



FoamTape

Product

Double sided adhesive foam tape with a release foil on one side, specially developed as part of the adhesive system for the bonding of wall cladding panels.

Applications

Provides first adhesion on cladding panels and guarantees sufficient thickness of the adhesive bead.

Features

- High bonding strength in various (weather)conditions.

Method of use

Once the primers have fully dried Simson FoamTape is applied only vertically to the support construction without any interruptions. For the correct position and length of the foam tape please take into account the dimensions of the supports, the panel dimensions and the necessary space for the adhesive beads. Press FoamTape firmly onto the support construction and cut to length with a sharp knife. After application of the FoamTape the release foil must not be removed immediately; only after the adhesive has been applied (and the cladding panels can be bonded) remove the release foil.

Hereafter the panel should be placed within the prescribed time.

Position the panel. Correction is still possible until the panel touches the foam tape. For good and easier positioning eventually use a joint spacer, supporting blocks or horizontal supporting laths. For easier handling a glass suction clamp also can be useful. Once the panel is positioned correctly, the panel must be pressed down by gently rubbing over the entire length of the FoamTape. Now it is no longer possible to correct the panel position.

Application temperature: +5°C till +30°C.



FoamTape

Technical data

Thickness	3 mm
Width	12 mm
Foam	physically crosslinked polyolefin foam
Specific density	approx. 60 kg/m ³
Release foil	siliconised paper (with Simson logo printed on top)
Application temperature	+5°C till +30°C
Shear strength	approx. 0,27 N/mm ²
Tensile strength	approx. 0,27 N/mm ²

Colour
black

Packaging
rolls 25 metre

Article code
182771

Further information

Store cool, dry and frost-free in unopened original packaging. Can be stored for 12 months.

Informatie aanvraag

The following publications are available on request:

- Material Safety Data Sheet (MSDS)

Bostik B.V.

Postbus 303
5201 AH 's-Hertogenbosch
Tel: +31 (0)73 6 244 244
Fax: +31 (0)73 6 244 344
E-mail: infonl@bostik.com
Internet: www.bostik.nl

Bostik Belux SA-NV

Meulestedekaai 86
B-9000 Gent
Tel: +32 (0)9 255 17 00
Fax: +32 (0)9 255 17 01
E-mail: info@bostik.be
Internet: www.bostik.be