



SNICKERISPACKEL

PRODUCT DESCRIPTION

A ready-mixed, quick drying acrylate plaster.

USES

For wood- and carpentrywork indoor. Strong adhesion.
Easy to grind. Can be broad-filled on larger surfaces.

TECHNICAL DATA

Filler	White dolomite-marble
Grain size	0 - 0.03 mm
Bonding agent	Polymer dispersion
Dilution	Water. Should normally not be diluted
Density	1.8
Drying	Approx.1 hour at room temperature
Cleaning	The tools are cleaned with water
Storage	Cool but frostless
Storage time	Approx.12 months in unopened package at +20°C. Does not spread or maintain fire.

WORKING INSTRUCTIONS

To be applied by hand with a steeledged spatula.
Painted surfaces must be washed, grounded or grinded.
New wood material should be grounded.
Metallic surfaces shall be protected against corrosion.
Grinding and painting can be done after approximately
1 hour.

SAFETY

The contents of the product is according to valid legislation
not classified as unhealthy or hazardous.
For further information, please see material safety data sheet.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.