



# WALL FABRIC 70

## TECHNICAL DATASHEET

Version: 2017-03-27

### PRODUCT DESCRIPTION

Wall adhesive made from PVAc/starch base. Adheres well to most surfaces. If the surface is a vinyl wallpaper, the vinyl layer must be removed before hanging the wallpaper.

### AREA OF USAGE

In dry areas for fibreglass wall coverings and acrylic structural wallpaper with a backing of made of paper. Vinyl wall coverings with a backing of made of paper, polyester, fibreglass or fabric. The substrate may be absorbent such as chipboard, plasterboard, etc., or it may be sealed such as a painted surface

### WORKING INSTRUCTION

1. Read the material manufacturer's usage instructions. Remove any loose wallpaper and peeling paint. Spackle and sand any unevenness. Highly absorbent substrates should be prepared with a mixture of 1 part adhesive and 3 parts water. Painted surfaces should be washed with a paint wash or similar product. Rinse well. 2. Bonding (hanging with adhesive) Fibreglass wall coverings (without paper backing)&colon; Roll on the adhesive on the wall in a smooth, rich layer. Attach the wallpaper while the adhesive is sticky. Avoid the penetration of the adhesive into the fabric. Any painting should not be done until one day later (at the earliest) or when the fabric is completely dry. Vinyl and acrylic structural wallpaper, vinyl wallpaper with a paper backing&colon; Unless otherwise instructed by the manufacturer, roll an even layer of the adhesive on the rear side of the wallpaper. Let the length to be folded sit for a few minutes. If the wallpaper is cleanly cut – hang edge-to-edge. Vinyl wall coverings with a backing of polyester, fibreglass or fabric&colon; Roll the adhesive on to the wall. If the wallpaper is cleanly cut – hang edge-to-edge. Overlap gluing of vinyl wallpaper is to be made with Bostik 78 Wet Room Adhesive. 3. Squeeze out any air bubbles carefully, with a plastic or steel putty knife. Work from the centre to the edges. Check to ensure that there is sufficient adhesive in all joints.

### SAFETY

The product's contents are not classed as hazardous to health or flammable according to applicable legislation. For additional information, refer to the Safety Data Sheet.

### CONTACT US

TEL +46 (0)42-19 50 00  
info.se@bostik.com



## TECHNICAL DATA

Adhesive type	Simple adhesive
Binder	PVAc and starch
Solvent	Water
Consistency	Thixotrope
Colour	White
Application tools	Roller or brush
Working temperature	Not lower than &plus;18°C
Cleaning agent	Water
Density	1.05 g/cm <sup>3</sup>
Solids content	19 ± 1&percnt; by weight
Adhesive usage	Approx. 3-6 m <sup>2</sup> /litre depending upon the material and method of application.
Thinner	Water. The adhesive should not be thinned
Flammable	No
Shelf life	12 months at &plus;10°C to 20°C in an unopened package. Protect from freezing.

## CONTACT US

TEL 042-19 50 00

[info.se@bostik.com](mailto:info.se@bostik.com)

